



Aim solo power cable

Not getting enough current through your OBDII connection? Add this direct power cable and never worry about charging before an event again. Vehicle Applications: 1990-2005 Mazda Miata 1.6L NA6 & 1.8L NA8, NB1, & NB2

The AiM Solo 2 is the most widely used lap timer and data logger in motorsport - used by hobbyists and professionals to improve their performance on the race track. Key Features : Integrated GPS configurable RGB LEDs Wi-fi Graphical Display 4GB Memory Open or Closed track creation Database with over 4000 Tracks worldwide ... Solo 2 power cable ...

AiM Solo 2/Solo 2 DL GPS lap timer/Dash logger aim-sportline Ver. 1.13. 6/7 In the box Solo 2, power cable with car lighter socket, battery charger with AC adapter, mounting bracket with screws. User manual & Race Studio 3 software freely ...

AiM Solo 2 & Solo 2 DL Power Cable with AC Adapter EU Plug The AiM Solo 2 & Solo 2 DL EU mains charger & power lead is used for charging from European mains power. Key Features : 5 pin - 712 male binder connection EU 2-pin plug Suitable for Solo 2 & Solo 2 DL 12V Solo 2 / Solo 2 DL EU Power Cable The Ai

OBDII External Power Cable. The AiM OBDII 2m external power cable is used to make your AiM device, Solo 2 DL communicate with the vehicle ECU. This is one of the connection cables available for the Solo 2 DL. Others are the RS232/CAN and the RPM cable. Some of the OBDII protocol channels received are RPM, Vehicle speed, Fuel level, Throttle ...

Solo 2 DL: Solo 2 DL, power cable with AC adapter, mounting bracket with screws, user manual, software installation CD, Aim sticker. ... With any purchase of an AiM Solo 2 or Solo DL 2, you can choose to include an AAF Solo Mount (normally a \$35.50 cost) for only \$10!

Solo external power cable is available in two versions: o 120 cm (47.2 inches) external power cable V02569060 o 300 cm (118.1 inches) external power cable V02569030 Solo external power cable is equipped with a 3 pins Binder 712 male connector on one side and a 12V car lighter plug on the other side.

The AiM external power cable fits the AiM Solo GPS Lap Timer. It features a 3-pin 712 male binder connection, which goes into the Solo GPS Lap Timer. The un-terminated wires allow you to connect to an external battery. This allows Solo GPS Lap Timer to have longer running times.

The AiM OBDII 2m external power cable is used to make your AiM device, Solo 2 DL communicate with the vehicle ECU. This is one of the connection cables available for the Solo ...

Pre-assembled AiM Solo / Solo 2 DL cable to be used in conjunction with our 4-pin plug and play adapters.



Aim solo power cable

Out of stock. SKU: Adpt-0004 Categories: E39, ... Be the first to review "AiM Solo DL External Power & CAN-Bus Cable, 4-pin, 2m" Cancel reply. Your rating * ...

AiM Solo 2 DL RPM & External Power Lead The AiM PRM cable is used for vehicles when the particular ECU is not supported. Key Features : 8 pin - 712 male binder connection 3 free cables Suitable for Solo 2 DL RPM External Power Cable In the unlikely event, your particular ECU is not supported you can connect the Sol

4 days ago; Power cable with wired car lighter socket for: Solo 2 and Solo 2 DL. Quick link Quick link English English Italiano Menu Compare ... Address : AiM Official Store Via Guido Cavalcanti, 8 20063 Cernusco sul Naviglio Milano Italy; Phone : +39 02.9290571; This site uses cookies. By continuing use this site, you are agreeing to our use of cookies.

The AiM external power cable fits the AiM Solo GPS Lap Timer. It features a 3-pin 712 male binder connection, which goes into the Solo GPS Lap Timer. The un-terminated wires allow you to connect to an external battery. This allows Solo ...

The power cable that comes with the AiM Solo 2 in the package is set up for a cigarette lighter connection, but this is a hard wire connection for true race cars. This harness connects your AiM Solo 2 to your vehicle's fuse box wiring. One end has a 5-pin 712 (screw-in) connector to fit the Solo, and the other has 2 non-terminated wires (Power ...

Power cable with wired car lighter socket for Solo 2/Solo 2 DL. Discover. Roll-bar kit for Solo 2/Solo 2 DL ... RPM + external power cable for Solo 2 DL. EXPANSIONS. Discover. SmartyCam 3 Sport. Discover. ACC2 Open. Discover. ACC2. ... competitor director at Formula Drift shows us data collection with Race Studio 3 and AiM Solo 2 DL. Watch Now ...

The accessory items shown here are all designed to work with the original AiM Solo and SoloDL lap timers. Most will not work with the current Solo2 / Solo2DL. Recent Top Seller for this product group ... AiM CAN 3-Pin to DC (Lighter Plug) Power Cable for Solo: \$39.99: In Stock: MC-575 . AiM 7-Pin 712 to DC (Lighter Plug) Cable for SoloDL ...

Solo 2 DL; Power Cable with AC Adaptor; Mounting Bracket with Screws; Aim Sticker; Choice of Power Leads Available as Selected at Checkout. Only One Supplied; User Manual; CAN/K-Line External Power Cable with OBDII Connector; CAN/RS232 external power cable; RPM external power cable (if your vehicle has no ECU)

AiM Solo 2 DL CAN / RS232 2M External Power Cable Motorcycle The AiM CAN/RS232 2m external power cable connects your Solo 2 DL to your ECU wiring. Key Features : 7 pin - 712 male binder connection 6 non-terminated ...



Aim solo power cable

The power cable that comes with the AiM Solo in the package is set up for a cigarette lighter connection, but this is a hard wire connection for true race cars. This harness connects your AiM Solo to your vehicle's fuse box wiring. One end has a 3-pin 712 (screw-in) connector to fit the Solo, and the other has 2 non-terminated wires (Power and ...

Shop our range of high-quality Motorcycle Solo Cables & Chargers to enhance your motorsport racing setup - next day delivery options available online today. Aim Shop Mychron 5, MXG, MXS MXL, Evo 4, Smartcam, Pressure and temperature Sensors, Solo GPS Lap timers, data loggers and racing sensors ... AiM Solo External Power Lead 3 Pin Unterminated ...

The power cable that comes with the AiM Solo 2 in the package is set up for a cigarette lighter connection, but this is a hard wire connection for true race cars. This harness connects your AiM Solo2 DL to your vehicle's fuse box wiring. One end has a 5-pin 712 (screw-in) connector to fit the Solo, and the other has 2 non-terminated wires ...

AIM Solo is an automatic lap timer based on GPS technology. It locates its GPS position, identifies the track from the internal list of the main world tracks and starts automatically sampling lap times. ... Solo USB cable (2) USB/AC power adapter (3) 2m OBDII/power cable (7) Mounting bracket with screws (6) Software installation CD: SoloDL: Kit ...

KIT SOLO 2/SOLO 2 DL: CABLE: Part number: V02589090: On RaceStudio 3 ... The bracket can be used with Solo 2 and Solo 2 DL. The bracket is only compatible with RSV4 original triple clamp. CABLE + BRACKET: Part number: V02589090CS: DOWNLOAD USER MANUAL ... AiM Tech srl will not be held responsible for any consequence that may result from the ...

Web: <https://www.derickwatts.co.za>

Chat online: <https://tawk.to/chat/667676879d7f358570d23f9d/1i0vbu11i?web=https://www.derickwatts.co.za>